HOLES IN UNDE RCOUNTER FIXTURE ARE OVERSIZED. DRILL FITTING HOLES IN COUNTER ACCORDING TO FITTING ROUGH-IN.
台下式脸盆龙头安装孔较大。根据安装尺寸图在台面上钻安装孔。

FAUCET HOLE CENTERLINE
龙头孔中心线

CENTERLINE OF LAVATORY
脸盆中心线

325mm

科勒 THE BOLD LOOK OF KOHLER®
全 球 厨 卫 经 典

K-2885T-8U
曼司 MAN'S LAV

铸铁台下脸盆
ENAMELED CAST IRON UNDERCOUNTER LAVATORY
切割图/安装说明书
CUT-OUT TEMPLATE / INSTALLATION INSTRUCTION

安装之前

注意

本说明书包含重要的保养、清洁方面的信息，请留交用户保管。

台下式脸盆的安装需由受过训练，经验丰富的人员来完成。

安装之前，开启新脸盆的包装，仔细检验脸盆是否有损坏，再将脸盆放回包装盒内，到安装时才取用。

该铸铁脸盆十分沉重，须请人帮忙一起搬动及安放。

切勿将胶水或粘性密封胶与本产品一起使用。

以下近似尺寸仅供参考；

脸盆内径.....610mm x 330mm
脸盆深度.....108mm
排水孔.....直径43mm

尺寸图 ROUGH-IN



推荐工具及材料(不随货供应)

护眼镜
安全鞋
铅笔
剪刀
卷尺
涂油灰刀
螺丝刀
孔锯
匙孔线锯或手提电锯
电钻(13mm即1/2" 或更大直径钻头)
密封胶

BEFORE YOU BEGIN

NOTES

These instructions contain important care, cleaning, and warranty information – please leave instructions for the consumer.

Due to the nature of the installation, undercounter lavatories should be installed by trained and experienced installers.

Prior to installation, unpack the new lavatory and carefully inspect it for damage. Return the lavatory to its protective carton until you are ready to install it.

Cast iron lavatories are very heavy. Get help lifting the lavatory into place.

Do not use adhesives or adhesive sealants with this product.

The following approximate measurements are for comparison only:

Lavatory basin area.....610mm x 330mm
lavatory water depth 108mm
Outet.....43mm D.

尺寸注释
产品尺寸为标定值，误差符合ASME/ANSI 标准A112.19。
(T) 提拉式排水343mm
(S) 254mm(根据305mm盆口计算，须按实际情况调整)
台下式脸盆龙头安装孔较大。根据安装尺寸图在台面上钻安装孔。

Roughing-In Notes
Fixture dimensions are nominal and conform to toler-ances in ASME/ANSI Standard A112.19 "
(T) Pop-up drain 13-1/2 "
(S) 10(Based on 12 " riser which may require cutting).
Holes in undrcounter fixture are oversized. Drill fitting holes in counter according to fitting rough-in.

TOOLS AND MATERIALS REQUIRED(Not supplied)

Safety glasses
Safety shoes
Pencil
Scissors
Tape measure
Putty knife
Screwdriver
Hole saw
Keyhole saw or saber saw
Drill (1/2" dia. drill bit or larger)
Sealant

安装

注意：选定理想的脸盆位置，确保防溅水板、龙头、脸盆和储物柜之间有足够的距离。

如图1所示，用软性铅笔沿模板在台面上 划线。切割图上标有中心线，以助对齐。

在台面上确定龙头孔中心线位置。(图3)

沿铅笔线小心切开台面。(图4)

暂将脸盆放入台面开口，校正位置。

注意：这将有助于确定在何处涂抹密封胶。

将脸盆从台面开口处移开。

钻龙头孔，孔必须相距102mm，直径介于35至38mm之间，以安装适合科勒龙头。

根据说明书将龙头安装上台面。

将大理石或其他硬质材料台面反转放置于泡沫垫上。在图示位置钻孔，直径10mm，深16mm。使用安装工具将锚冲子置入孔内。用锤子敲击安装工具，将锚冲子安装到位。

注意：内置冲子必须妥善安装，以保证最终的安装效果。

注意：若为木质台面，在图示位置预先钻好木螺丝孔。

注意：木质台面下方外露区域需进行防水处理。

涂脸盆与台面接触区域一周涂上一条密封胶。使用合适的安装五金件将脸盆安装上台面。将脸盆对齐台面开口，然后上紧夹子，直至脸盆边缘与台面紧密结合。切勿过分上紧。用干净抹布擦去多余密封胶。

FIG #1 图1

FIG #2 图2



FIG #3 图3

FIG #4 图4



FIG #5 图5

FIG #6 图6

INSTALLATION

NOTE: Check for adequate clearance between the backsplash, faucet, fixture, and cabinet.

Cut out the template and mounting hole locations with a scissors inside the cutting line, as shown.

Trace the template on the countertop using a soft lead pencil. Centerlines are provided to help align the opening.

Locate the faucet hole centerline on the countertop.

Cut out the opening by carefully following the pencil line traced from the template.

Temporarily place the lavatory in the countertop cutout to check for fit.

NOTE: This will serve as a guide for applying sealant.

Remove the lavatory from the countertop cutout.

Drill the faucet holes. The faucet holes must be 4" apart and between 1-3/8" and 1-1/2" in diameter for Kohler lavatory faucets.

Install the faucet to the countertop, following the manufacturer's instructions.

Set marble or solid surface countertops upside down on foam padding. Drill 3/8" diameter holes, 5/8" deep in the locations shown. Set the lead anchors into the holes using a setting tool. Tap the setting tool with a hammer to set the lead anchors into position.

NOTE: The insert must be properly installed to ensure proper fit.

NOTE: For wood countertops, pre-drill the holes for wood screws in the locations shown.

NOTE: waterproof unprotected overhang area on the underside of wood counter.

Apply a bead of sealant around the entire area where the lavatory contacts the countertop. Install the lavatory to the countertop using the appropriate hardware. Position the lavatory squarely under the cutout before tightening the clips. Draw the rim up to the countertop until it is snug. Do not overtighten. Wipe away any excess sealant with a clean cloth.

使用密封胶后需待至少三十分钟，让密封胶干透。连接排水及龙头供水组件。打开龙头，检查所有连接处是否有渗漏。

编号	零配件编号	描述
1	44596	冲子
2	44597	夹子
3	68918	螺钉
4	44598	螺钉



Allow the sealant to set for 30 minutes or longer. Connect the drain fittings and faucet supply fittings. Turn on the water, and check for leaks at all the connections.

ITEM NO.	PART NO	DESCRIPTION
1	44596	Insert
2	44597	Clip
3	68918	Screw
4	44598	Screw

用户须知(护理和清洁)

优质的科勒釉面经高温烧制，与铸铁紧密融合，表面坚硬，色彩厚实亮丽，外观出众，易于维护，比塑料更加耐用。

为保持脸盆光洁如新，须确保每次使用后彻底冲洗干净，**切勿使用腐蚀性的清洁剂**，以免刮花及破坏脸盆的表面。要清除顽固污垢，油漆或粘油，可使用松油或油漆稀释剂。

陶瓷及浴缸产品及配件担保——年有限担保

科勒公司担保其陶瓷及浴缸产品及配件在制造工艺上无瑕疵。

本产品自购买之日起即获得本公司一年的质量保证。在质保期内，凭购货发票，科勒公司将免费承担由制造质量引起的任何问题。经核查后，科勒中国有限公司有权决定是修理、更换、还是作适当的调整。

这里所指的担保，包括产品，都已明确地限制在该担保期之内。科勒中国有限公司对其后出现的损坏不负有任何责任。担保也不包括外观损伤，使用不当以及未按说明书安装的损失。

为获得快捷的担保服务，请联系您的销售商；您也可写信给科勒中国有限公司(请出示销售发票原件作为购货凭证)：

科勒(中国)投资有限公司
中央客户服务中心
上海市卢湾区淮海中路138号
上海广场19楼
邮编：200021

这是我们全部的书面担保。

IMPORTANT CONSUMER INFORMATION (CARE AND CLEANING)

Quality Kohler enamel is fused to red-hot cast iron. The resulting glass-hard surface and lustrous depth of color is beautiful to look at, easy to care for, and more resistant to scratching than plastic materials.

To keep your lavatory looking new, make sure you rinse it out thoroughly after each use. DO NOT ABRASIVES on this product, as they will scratch and ruin the surface. Stubborn stains, paint, or tar can be removed with turpentine or paint thinner.

Plumbing Fixtures and Fittings Limited One-year Warranty

Kohler plumbing fixtures and fittings are warranted to be free of manufacturing defects.

This product is warranted for one year from date of purchase. Kohler China will be responsible for any problems caused by manufacturing defects provided with the invoice. Kohler China will, at its election, repair, replace or make appropriate adjustment where Kohler China inspection discloses any such defects occurring in normal usage within one year after purchase.

Implied warranties including that of merchantability and fitness for a particular purpose are expressly limited in duration to the duration of this warranty. Kohler China disclaims any liability for special, incidental or consequential damages. Damages to the product caused by misuse, abuse and installation that is not in accordance with the owner's manual are not covered by this warranty.

To obtain quick warranty service, please contact your dealer or write to Kohler China. (Original sales receipt must be provided as the proof of purchase.)

Kohler China Investment Company Ltd.
Central Customer Service Center
19/F, Shanghai Square, 138 Huai Hai Road, Luwan District, Shanghai, PRC
Zip Code: 200021

This is our exclusive written warranty.

沿此线切割
CUT ALONG THIS LINE

脸盆边缘
RIM OF LAVATORY

When plotting template full size:
Make sure horizontal and vertical dimensions match the dimensions labeled on the template.
按实际大小标绘切割图时：确保横向及纵向尺寸与切割图上所标尺寸一致。

MOUNTING HARDWARE HOLE LOCATIONS (4 REQUIRED)
五金件安装孔位置(需要4个)

1035906-T01-A

版权为科勒中国有限公司所有，2004
Copyright Kohler China Ltd., 2004

622mm